



Configuration Matrix - HIGH AVAILABILITY

Physical & Virtualized Configuration

SilverBack® Node #1	
Server	Dual XEON Server (Or equivalent)
CPU	Dual 6 Core CPU (Virtualized - 6 Core Minimum)
Memory	32GB
OS	Minimum 512 GB Raid 5
Bucket/Cache	See Storage Server
Windows Server	2016 or Greater
SilverBack® Node #2	
Server	Dual XEON Server (Or equivalent)
CPU	Dual 6 Core CPU (Virtualized - 6 Core Minimum)
Memory	32GB
OS	Minimum 512 GB Raid 5
Bucket/Cache	See Storage Server
Windows Server	2016 or Greater
Database Server	
Server	Dual XEON Server (Or equivalent)
CPU	Dual 6 Core CPU (Virtualized - 6 Core Minimum)
Memory	96GB
OS	Minimum 5TB Raid 5
Bucket/Cache	2016 or Greater
Windows Server	2016 or Greater
Server or Customer Provided SAN	
Server	Dual XEON Server (Or equivalent)
CPU	Dual 6 Core CPU (Virtualized - 6 Core Minimum)
Memory	32GB
OS	Minimum 1TB Raid 5
Bucket/Cache	Minimum 20TB Raid 5
Windows Server	2016 or Greater
Local Traffic Manager or Equivalent Load Balancer	
Server	F5 2000S or similar
Note	<i>Must be able to monitor the 2 nodes and route traffic to either node if monitoring port returns an error or no response.</i>

As of August 1, 2022